



FAG

NU328-E-XL-M1-F1-C4

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	140 mm	Bore diameter
D	300 mm	Outside diameter
B	62 mm	Width
C _r	790.000 N	Basic dynamic load rating, radial
C _{0r}	800.000 N	Basic static load rating, radial
C _{ur}	95.000 N	Fatigue load limit, radial
n _G	3.950 1/min	Limiting speed
n _{gr}	2.170 1/min	Reference speed
≈m	21,98 kg	Masa



Mounting dimensions

d a min	157 mm	Minimum diameter shaft shoulder
d a max	176 mm	Maximum diameter of shaft shoulder
d b min	182 mm	Minimum shaft shoulder
D a max	283 mm	Maximum diameter of housing shoulder
r a max	3 mm	Maximum recess radius
r a1 max	3 mm	Maximum recess radius

Dimensions

r min	4 mm	Minimum chamfer dimension
r 1 min	4 mm	Minimum chamfer dimension
s	5,2 mm	Axial displacement
E	264 mm	Raceway diameter outer ring
F	180 mm	Raceway diameter inner ring
D 1 min	251,7 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia