



FAG

NUP2222-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NUP...-E-XL-M1, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	200 mm	Outside diameter
B	53 mm	Width
C _r	455.000 N	Basic dynamic load rating, radial
C _{0r}	520.000 N	Basic static load rating, radial
C _{ur}	88.000 N	Fatigue load limit, radial
n _G	6.100 1/min	Limiting speed
n _{gr}	2.750 1/min	Reference speed

≈m 7,958 kg Masa



Mounting dimensions

d 1	141,55 mm	Maximum rib diameter inner ring
D 1 min	173,82 mm	Minimum rib diameter outer ring
d a min	122 mm	Minimum diameter shaft shoulder
d c min	144 mm	Minimum shaft shoulder
D a max	188 mm	Maximum diameter of housing shoulder
r a max	2 mm	Maximum recess radius

Dimensions

r min	2,1 mm	Minimum chamfer dimension
r 1 min	2,1 mm	Minimum chamfer dimension
E	180,5 mm	Raceway diameter outer ring
F	132,5 mm	Raceway diameter inner ring

B 3	8,5 mm	Width of loose rib
-----	--------	--------------------

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia