




FAG

NUP240-E-M1-C3

Cylindrical roller bearing

Cylindrical roller bearing NUP...-E-M1, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

Informacje techniczne





Twoja aktualna wersja produktu

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	200 mm	Bore diameter
D	360 mm	Outside diameter
B	58 mm	Width
C _r	750.000 N	Basic dynamic load rating, radial
C _{0r}	1.040.000 N	Basic static load rating, radial
C _{ur}	124.000 N	Fatigue load limit, radial
n _G	2.900 1/min	Limiting speed
n _{gr}	1.600 1/min	Reference speed
≈m	28,3 kg	Masa





Mounting dimensions

d_1	257,6 mm	Maximum rib diameter inner ring
$D_1 \text{ min}$	311,5 mm	Minimum rib diameter outer ring
$d_a \text{ min}$	217 mm	Minimum diameter shaft shoulder
$d_c \text{ min}$	261 mm	Minimum shaft shoulder
$D_a \text{ max}$	343 mm	Maximum diameter of housing shoulder
$r_a \text{ max}$	3 mm	Maximum recess radius

Dimensions

r_{min}	4 mm	Minimum chamfer dimension
$r_1 \text{ min}$	4 mm	Minimum chamfer dimension
E	323 mm	Raceway diameter outer ring
F	243 mm	Raceway diameter inner ring
B_3	9 mm	Width of loose rib

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe