


NX30-Z-XL

Needle roller/axial ball bearing

Needle roller/axial ball bearings NX...-Z,
single direction axial component, for grease
lubrication

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Z	Bearing with end cap
Cage	Standard	

Main Dimensions & Performance Data

F_w	30 mm	Bore diameter
D	42 mm	Outside diameter
C	30 mm	Height
C_r	25.500 N	Basic dynamic load rating, radial
C_{0r}	36.000 N	Basic static load rating, radial
C_a	11.700 N	Basic dynamic load rating, axial
C_{0a}	28.000 N	Basic static load rating, axial
C_{ur}	6.400 N	Fatigue load limit, radial
C_{ua}	1.270 N	Fatigue load limit, axial
n_G	4.300 1/min	Limiting speed
$\approx m$	121,25 g	Masa



Mounting dimensions

d _a	36,5 mm	Mounting dimension shaft shoulder
r _{a max}	0,3 mm	Maximum recess radius
D ₁	45,1 mm	Connection diameter snap ring
C ₂	14,2 mm	Connection width with snap ring

Dimensions

C ₁	10 mm	Distance to lubrication hole
C ₂	10 mm	Distance to lubrication hole
d _w	30 mm	Bore diameter of shaft washer
r _{min}	0,3 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

IR25X30X20-XL	Suitable inner rings IR
WR42, SW42	Snap ring

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Uszczelnienie jednostronne