



PCSLT30-XL

Flanged housing unit

Housing units PCSLT, two-bolt flanged housing units, sheet steel, eccentric locking collar, P seals

X-life

Informacje techniczne

Twoja aktualna wersja produktu

Material Steel sheet

Main Dimensions & Performance Data

d	30 mm	Bore diameter
L	84 mm	Flange width
H	112,5 mm	Height flange
U	29 mm	Total height unit
C _r	13.200 N	Basic dynamic load rating, radial
C _{0r}	8.300 N	Basic static load rating, radial
C _{0r G}	6.000 N	Load carrying capacity (housing)
≈m	0,32 kg	Masa

Mounting dimensions

J	90,5 mm	Distance fixing bore
N	11,5 mm	Fixing square
n	2	Number of screwing holes



Dimensions

A	16 mm	Height housing
A ₂	9 mm	Distance raceway
S ₁	3,5 mm	Thickness
S	2,5 mm	Thickness of flange

Additional information

1	Number of housings
1	Number of housings 2
FLAN55-CSLT	Housing
FLAN55-CST	Housing (Part 2)
RALE30-XL-NPP-B	Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.