





RCJT45-XL

Flanged housing unit

Housing units RCJT, two-bolt flanged housing units, cast iron, eccentric locking collar, R seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	45 mm	Bore diameter
L	111 mm	Flange width
H	180 mm	Height flange
U	59,1 mm	Total height unit
C _r	34.500 N	Basic dynamic load rating, radial
C _{0r}	20.400 N	Basic static load rating, radial
C _{ur}	970 N	Fatigue load limit, radial
≈m	1,9 kg	Masa

Mounting dimensions

J	148,5 mm	Distance fixing bore
N	14 mm	Fixing bore
n	2	Number of screwing holes
W	5 mm	Width of flats



Dimensions

A	35 mm	Height housing
A 1	13 mm	Thickness of flange
A 2	24 mm	Distance raceway
B 1	56,5 mm	Locking collar total width
V	111 mm	Shoulder diameter housing
Q	M6	Connection thread for lubrication
d 3	63 mm	Outside diameter locking collar

Additional information

1	Number of housings
CJT09	Housing
GE45-XL-KRR-B	Bearing designation

Temperature range

T min	-20 °C	Operating temperature min.
T max	120 °C	Operating temperature max.