



**RCJTZ20-XL**

Flanged housing unit

Housing units RCJTZ, two-bolt flanged housing units, cast iron, centring spigot, eccentric locking collar, R seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	20 mm	Bore diameter
L	60,5 mm	Flange width
H	112,5 mm	Height flange
U	45,6 mm	Total height unit
C _r	12.800 N	Basic dynamic load rating, radial
C _{0r}	6.600 N	Basic static load rating, radial
C _{ur}	315 N	Fatigue load limit, radial
≈m	0,61 kg	Masa

Mounting dimensions

J	90 mm	Distance fixing bore
N	11,5 mm	Fixing bore
T ₁	3,5 mm	Height spigot
Z	55 mm	Diameter spigot
	h8	Diameter spigot clearance
n	2	Number of screwing holes



Dimensions

A	31,7 mm	Height housing
A ₁	11 mm	Thickness of flange
A ₂	19 mm	Distance raceway
V	60,5 mm	Shoulder diameter housing
Q	M6	Connection thread for lubrication
d ₃	33 mm	Outside diameter eccentric locking collar

Additional information

1	Number of housings
CJTZ04	Housing
GE20-XL-KRR-B	Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.