


RNA4903-2RSR-XL

Radial roller bearing

Needle roller bearings RNA...-2RSR, lip seals on both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Lubrication hole	With	With
Coating	Without	
Sealing	2RSR	Contact seal on both sides
Special features	Without	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

F _w	22 mm	Under roller diameter
D	30 mm	Outside diameter
B	13 mm	Width
C _r	10.000 N	Basic dynamic load rating, radial
C _{0r}	11.000 N	Basic static load rating, radial
C _{ur}	2.220 N	Fatigue load limit, radial
n _G	12.000 1/min	Limiting speed
n _G Grease	12.000 1/min	Limiting speed for grease lubrication

≈m	23,27 g	Masa
----	---------	------



Dimensions

r _{min}	0,3 mm	Minimum chamfer dimension
C	13 mm	Width, outer ring

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Mała przestrzeń zabudowy