


RNA4905-2RSR-XL

Radial roller bearing

Needle roller bearings RNA...-2RSR, lip seals on both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Lubrication hole	With	With
Coating	Without	
Sealing	2RSR	Contact seal on both sides
Special features	Without	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

F _w	30 mm	Under roller diameter
D	42 mm	Outside diameter
B	17 mm	Width
C _r	21.800 N	Basic dynamic load rating, radial
C _{0r}	24.200 N	Basic static load rating, radial
C _{ur}	4.650 N	Fatigue load limit, radial
n _G	8.600 1/min	Limiting speed
n _G Grease	8.600 1/min	Limiting speed for grease lubrication

≈m	0,063 kg	Masa
----	----------	------



Dimensions

r _{min}	0,3 mm	Minimum chamfer dimension
C	17 mm	Width, outer ring

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Mała przestrzeń zabudowy