
**RNA4906-RSR-XL**

Needle roller bearing

Needle roller bearings RNA...-RSR, lip seal on one side

**X-life**

## Informacje techniczne



## Twoja aktualna wersja produktu

|              |          |
|--------------|----------|
| Cage         | Standard |
| Cage feature | Standard |

## Main Dimensions &amp; Performance Data

|             |             |                                   |
|-------------|-------------|-----------------------------------|
| $F_w$       | 35 mm       | Under roller diameter             |
| D           | 47 mm       | Outside diameter                  |
| C           | 17 mm       | Width, outer ring                 |
| $C_r$       | 23.900 N    | Basic dynamic load rating, radial |
| $C_{0r}$    | 28.500 N    | Basic static load rating, radial  |
| $C_{ur}$    | 5.500 N     | Fatigue load limit, radial        |
| $n_G$       | 7.500 1/min | Limiting speed                    |
| $\approx m$ | 70 g        | Masa                              |

## Dimensions

|           |        |                           |
|-----------|--------|---------------------------|
| $r_{min}$ | 0,3 mm | Minimum chamfer dimension |
|-----------|--------|---------------------------|

## Temperature range

|           |        |                            |
|-----------|--------|----------------------------|
| $T_{min}$ | -20 °C | Operating temperature min. |
| $T_{max}$ | 100 °C | Operating temperature max. |



### Właściwości

---



Obciążenie promieniowe



Smarowanie smarem



Uszczelnienie jednostronne



Mala przestrzeń zabudowy