



RNA6901-XL

Radial roller bearing

Needle roller bearings RNA, to DIN 617/ISO 1206

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Lubrication hole	With	With
Coating	Without	
Sealing	Without	
Special features	Without	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

F _w	16 mm	Under roller diameter
D	24 mm	Outside diameter
B	22 mm	Width
C _r	18.100 N	Basic dynamic load rating, radial
C _{0r}	21.600 N	Basic static load rating, radial
C _{ur}	3.850 N	Fatigue load limit, radial
n _G	23.200 1/min	Limiting speed
n _G Grease	13.900 1/min	Limiting speed for grease lubrication
n _{gr}	14.300 1/min	Reference speed
m	31,2 g	Masa



Dimensions

r _{min}	0,3 mm	Minimum chamfer dimension
C	22 mm	Width, outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

G16X24X3	Sealing ring
SD16X24X3	Sealing ring 2

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Mala przestrzeń zabudowy