


RNA6907-ZW-XL

Radial roller bearing

Needle roller bearings RNA, to DIN 617/ISO 1206

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Lubrication hole	With	With
Coating	Without	
Sealing	Without	
Special features	Without	
Number of rows	ZW	Double-row design

Main Dimensions & Performance Data

F_w	42 mm	Under roller diameter
D	55 mm	Outside diameter
C_r	54.000 N	Basic dynamic load rating, radial
C_{0r}	86.000 N	Basic static load rating, radial
C_{ur}	16.200 N	Fatigue load limit, radial
n_G	10.700 1/min	Limiting speed
$n_{G\text{ Grease}}$	6.400 1/min	Limiting speed for grease lubrication
n_{gr}	6.200 1/min	Reference speed
m	0,199 g	Masa



Dimensions

r _{min}	0,6 mm	Minimum chamfer dimension
C	36 mm	Width, outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy