


RNA6908-ZW-XL

Radial roller bearing

Needle roller bearings RNA, to DIN 617/ISO 1206

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Lubrication hole	With	With
Coating	Without	
Lubricant	Without	
Sealing	Without	
Special features	Without	
Number of rows	ZW	Double-row design



Main Dimensions & Performance Data

F _w	48 mm	Under roller diameter
D	62 mm	Outside diameter
C _r	74.000 N	Basic dynamic load rating, radial
C _{0r}	116.000 N	Basic static load rating, radial
C _{ur}	19.800 N	Fatigue load limit, radial
n _G	9.200 1/min	Limiting speed
n _G Grease	5.500 1/min	Limiting speed for grease lubrication
n _{gr}	5.400 1/min	Reference speed
m	260,54 g	Masa

Dimensions

r _{min}	0,6 mm	Minimum chamfer dimension
C	40 mm	Width, outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Mala przestrzeń zabudowy