



SL024876

Cylindrical roller bearing

Cylindrical roller bearing SL02...-A, full complement roller set, two-row, non-locating bearing, 0 ribs on outer ring (smooth), 3 ribs on inner ring, type SL02

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	380 mm	Bore diameter
D	480 mm	Outside diameter
B	100 mm	Width
C _r	1.320.000 N	Basic dynamic load rating, radial
C _{0r}	3.500.000 N	Basic static load rating, radial
C _{ur}	365.000 N	Fatigue load limit, radial
n _G	710 1/min	Limiting speed
n _{gr}	375 1/min	Reference speed
m	44 kg	Masa

Mounting dimensions

d _{c min}	419 mm	Minimum shaft shoulder
d _{a min}	419 mm	Minimum diameter shaft shoulder
D _{e min}	455,5 mm	Minimum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum recess radius



Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
s	6 mm	Axial displacement
C	50 mm	Distance to lubrication hole
d _{1 max}	419 mm	Maximum rib diameter inner ring
E	455,8 mm	Raceway diameter outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

NNCL4876V	Bearing designation DIN5412
-----------	-----------------------------

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe