



SL045004-C3

Cylindrical roller bearing

Cylindrical roller bearing SL04, full complement roller set, two-row, locating bearing, central rib on outer ring, 3 ribs on inner ring, type SL04

Informacje techniczne

Twoja aktualna wersja produktu

Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	20 mm	Bore diameter
D	42 mm	Outside diameter
B	30 mm	Width
C _r	41.500 N	Basic dynamic load rating, radial
C _{0r}	51.000 N	Basic static load rating, radial
C _{ur}	7.000 N	Fatigue load limit, radial
n _{G Grease}	5.500 1/min	Limiting speed for grease lubrication
m	185,3 g	Masa



Mounting dimensions

C _{a1}	21,5 mm	Mounting dim for snap ring WRE (not included in delivery) Tolerance: 0/-0,2
C _{a2}	21 mm	Mounting dim for retaining ring to DIN 471 (not incl. In delivery) Tol: 0/-0,2
d ₁	31 mm	Rib diameter inner ring
d ₂	34 mm	Sealing diameter (rib)
d ₃	47 mm	Outside diameter of snap ring WRE
d _{1 min}	31 mm	Minimum diameter shaft shoulder
	30 °	Chamfer angle
	-0,2 mm	Lower distance snap ring tolerance
	-0,2 mm	Lower distance retaining ring tolerance
	0 mm	Upper distance snap ring tolerance
	0 mm	Upper distance retaining ring tolerance
	0 mm	Lower distance ring groove tolerance
	0,2 mm	Upper distance ring groove tolerance

Dimensions

C	29 mm	Width, outer ring
C ₁	24,7 mm	Distance ring grooves
D ₁	39,8 mm	Diameter of groove
m	1,8 mm	Width of groove
r _{min}	0,3 mm	Minimum chamfer dimension
t	0,5 mm	Chamfer width
X	22,5 mm	Distance between rolling elements

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.