



SL045038-D-PP-2NR

Cylindrical roller bearing

Cylindrical roller bearing SL04...-D-PP-2NR, full complement roller set, two-row, locating bearing, central rib on outer ring, 3 ribs on inner ring, type SL04

Informacje techniczne

Twoja aktualna wersja produktu

Design	D	New outer Contour
Sealing	PP	Contact Seal on both sides
Holding Rings	2NR	Two retaining rings included
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	190 mm	Bore diameter
D	290 mm	Outside diameter
B	136 mm	Width
C _r	1.160.000 N	Basic dynamic load rating, radial
C _{0r}	2.210.000 N	Basic static load rating, radial
C _{ur}	275.000 N	Fatigue load limit, radial
n _G Grease	660 1/min	Limiting speed for grease lubrication
≈m	30,5 kg	Masa



Mounting dimensions

C _{a1}	110 mm	Mounting dim for snap ring WRE (not included in delivery) Tolerance: 0/-0,2
C _{a2}	108 mm	Mounting dim for retaining ring to DIN 471 (not incl. In delivery) Tol: 0/-0,2
d ₁	226,5 mm	Rib diameter inner ring
d ₂	248 mm	Sealing diameter (rib)
d ₃	312 mm	Outside diameter of snap ring WRE
d _{1 min}	226,5 mm	Minimum diameter shaft shoulder
	30 °	Chamfer angle
	-0,2 mm	Lower distance snap ring tolerance
	-0,2 mm	Lower distance retaining ring tolerance
	0 mm	Upper distance snap ring tolerance
	0 mm	Upper distance retaining ring tolerance
	0 mm	Lower distance ring groove tolerance
	0,2 mm	Upper distance ring groove tolerance

Dimensions

C	135 mm	Width, outer ring
C ₁	118,2 mm	Distance ring grooves
D ₁	284 mm	Diameter of groove
m	5,2 mm	Width of groove
r _{min}	0,6 mm	Minimum chamfer dimension
t	2 mm	Chamfer width
X	112 mm	Distance between rolling elements

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.