






SL1818/630-E-TB-C4

Cylindrical roller bearing

Cylindrical roller bearing, SL1818..-E-TB
full complement roller set, single row, semi-
locating bearing, 1 rib on outer ring, 2 ribs on
inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	TB	Bearings with increased axial load capacity
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	630 mm	Bore diameter
D	780 mm	Outside diameter
B	69 mm	Width
C _r	1.410.000 N	Basic dynamic load rating, radial
C _{0r}	3.150.000 N	Basic static load rating, radial
C _{ur}	285.000 N	Fatigue load limit, radial
n _G	425 1/min	Limiting speed
n _{gr}	260 1/min	Reference speed
m	68 kg	Masa



Mounting dimensions

$d_{a \min}$	680 mm	Minimum diameter shaft shoulder
$d_{c \min}$	680 mm	Minimum shaft shoulder
$D_{a \max}$	725,5 mm	Maximum diameter of housing shoulder
$D_{e \min}$	742,5 mm	Minimum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum recess radius
E	742,5 mm	Raceway diameter outer ring

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
s	7,5 mm	Axial displacement
d_1	680 mm	Maximum rib diameter inner ring
$D_1 \min$	725,6 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe