



SL1818/710-E-TB

Cylindrical roller bearing

Cylindrical roller bearing, SL1818..-E-TB
full complement roller set, single row, semi-
locating bearing, 1 rib on outer ring, 2 ribs on
inner ring, type SL18

Informacje techniczne




Twoja aktualna wersja produktu

Design	TB	Bearings with increased axial load capacity
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	710 mm	Bore diameter
D	870 mm	Outside diameter
B	74 mm	Width
C _r	1.730.000 N	Basic dynamic load rating, radial
C _{0r}	3.950.000 N	Basic static load rating, radial
C _{ur}	345.000 N	Fatigue load limit, radial
n _G	375 1/min	Limiting speed
n _{gr}	215 1/min	Reference speed
m	87,14 kg	Masa





Mounting dimensions

d a min	765 mm	Minimum diameter shaft shoulder
d c min	765 mm	Minimum shaft shoulder
D a max	815 mm	Maximum diameter of housing shoulder
D e min	843,5 mm	Minimum diameter of housing shoulder
r a max	4 mm	Maximum recess radius
E	843,5 mm	Raceway diameter outer ring

Dimensions

r min	4 mm	Minimum chamfer dimension
s	7,5 mm	Axial displacement
d 1	765 mm	Maximum rib diameter inner ring
D 1 min	815,4 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe