



SL182216-A-BR-C3

Cylindrical roller bearing

Cylindrical roller bearing SL1822...-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant A
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	80 mm	Bore diameter
D	140 mm	Outside diameter
B	33 mm	Width
C _r	223.000 N	Basic dynamic load rating, radial
C _{0r}	280.000 N	Basic static load rating, radial
C _{ur}	41.500 N	Fatigue load limit, radial
n _G	3.000 1/min	Limiting speed
n _{gr}	2.040 1/min	Reference speed
≈m	2,076 kg	Masa



Mounting dimensions

d _{a min}	98,5 mm	Minimum diameter shaft shoulder
d _{c min}	98,5 mm	Minimum shaft shoulder
D _{a max}	119 mm	Maximum diameter of housing shoulder
D _{e min}	126 mm	Minimum diameter of housing shoulder
r _{a max}	2 mm	Maximum recess radius
E	126,3 mm	Raceway diameter outer ring

Dimensions

r _{min}	2 mm	Minimum chamfer dimension
s	1,5 mm	Axial displacement
d ₁	98,6 mm	Maximum rib diameter inner ring
D _{1 min}	119,3 mm	Minimum rib diameter outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia