



SL182240

Cylindrical roller bearing

Cylindrical roller bearing SL1822...-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	200 mm	Bore diameter
D	360 mm	Outside diameter
B	98 mm	Width
C _r	1.410.000 N	Basic dynamic load rating, radial
C _{0r}	2.010.000 N	Basic static load rating, radial
C _{ur}	245.000 N	Fatigue load limit, radial
n _G	1.150 1/min	Limiting speed
n _{gr}	770 1/min	Reference speed
≈m	41,964 kg	Masa



Mounting dimensions

d a min	246,6 mm	Minimum diameter shaft shoulder
d c min	246,5 mm	Minimum shaft shoulder
D a max	302 mm	Maximum diameter of housing shoulder
D e min	319 mm	Minimum diameter of housing shoulder
r a max	4 mm	Maximum recess radius
E	319,4 mm	Raceway diameter outer ring

Dimensions

r min	4 mm	Minimum chamfer dimension
s	9 mm	Axial displacement
d 1	246,6 mm	Maximum rib diameter inner ring
D 1 min	302,4 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe