




SL182922-B-XL-C2

Cylindrical roller bearing

Cylindrical roller bearing SL18, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

X-life

Informacje techniczne





Twoja aktualna wersja produktu

Design	B	Internal Variant B
Radial internal clearance	C2 (Group 2)	Internal clearance smaller than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	150 mm	Outside diameter
B	24 mm	Width
C _r	155.000 N	Basic dynamic load rating, radial
C _{0r}	213.000 N	Basic static load rating, radial
C _{ur}	34.500 N	Fatigue load limit, radial
n _G	2.900 1/min	Limiting speed
n _{gr}	1.710 1/min	Reference speed
≈m	1,175 kg	Masa





Mounting dimensions

d a min	124 mm	Minimum diameter shaft shoulder
d c min	124 mm	Minimum shaft shoulder
D a max	136 mm	Maximum diameter of housing shoulder
D e min	141,5 mm	Minimum diameter of housing shoulder
r a max	1,1 mm	Maximum recess radius
E	141,5 mm	Raceway diameter outer ring

Dimensions

r min	1,1 mm	Minimum chamfer dimension
s	1,5 mm	Axial displacement
d 1	124 mm	Maximum rib diameter inner ring
D 1 min	136,2 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia