



SL182926-B-XL

Cylindrical roller bearing

Cylindrical roller bearing SL18, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

X-life

Informacje techniczne




Twoja aktualna wersja produktu

Design	B	Internal Variant B
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	180 mm	Outside diameter
B	30 mm	Width
C _r	238.000 N	Basic dynamic load rating, radial
C _{0r}	350.000 N	Basic static load rating, radial
C _{ur}	55.000 N	Fatigue load limit, radial
n _G	2.420 1/min	Limiting speed
n _{gr}	1.500 1/min	Reference speed
≈m	2,236 kg	Masa





Mounting dimensions

$d_{a\ min}$	146 mm	Minimum diameter shaft shoulder
$d_{c\ min}$	146 mm	Minimum shaft shoulder
$D_{a\ max}$	161 mm	Maximum diameter of housing shoulder
$D_{e\ min}$	167 mm	Minimum diameter of housing shoulder
$r_{a\ max}$	1,5 mm	Maximum recess radius
E	167,2 mm	Raceway diameter outer ring

Dimensions

$r_{\min}$	1,5 mm	Minimum chamfer dimension
s	2 mm	Axial displacement
d_1	146 mm	Maximum rib diameter inner ring
$D_1\ min$	161,1 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia