



SL182934-B-XL-BR

Cylindrical roller bearing

Cylindrical roller bearing SL18, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

X-life

Informacje techniczne




Twoja aktualna wersja produktu

Design	B	Internal Variant B
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	170 mm	Bore diameter
D	230 mm	Outside diameter
B	36 mm	Width
C _r	365.000 N	Basic dynamic load rating, radial
C _{0r}	540.000 N	Basic static load rating, radial
C _{ur}	85.000 N	Fatigue load limit, radial
n _G	1.830 1/min	Limiting speed
n _{gr}	1.190 1/min	Reference speed
≈m	4,021 kg	Masa





Mounting dimensions

d _{a min}	190,6 mm	Minimum diameter shaft shoulder
d _{c min}	190,5 mm	Minimum shaft shoulder
D _{a max}	211 mm	Maximum diameter of housing shoulder
D _{e min}	218 mm	Minimum diameter of housing shoulder
r _{a max}	2 mm	Maximum recess radius
E	218,5 mm	Raceway diameter outer ring

Dimensions

r _{min}	2 mm	Minimum chamfer dimension
s	2,5 mm	Axial displacement
d ₁	190,6 mm	Maximum rib diameter inner ring
D _{1 min}	211,3 mm	Minimum rib diameter outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia