





SL182964-B-C4

Cylindrical roller bearing

Cylindrical roller bearing SL18...-B, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	B	Internal Variant B
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	320 mm	Bore diameter
D	440 mm	Outside diameter
B	72 mm	Width
C _r	1.210.000 N	Basic dynamic load rating, radial
C _{0r}	2.340.000 N	Basic static load rating, radial
C _{ur}	260.000 N	Fatigue load limit, radial
n _G	820 1/min	Limiting speed
n _{gr}	495 1/min	Reference speed
m	32,32 kg	Masa



Mounting dimensions

$d_{a \min}$	359 mm	Minimum diameter shaft shoulder
$d_{c \min}$	359 mm	Minimum shaft shoulder
$D_{a \max}$	397 mm	Maximum diameter of housing shoulder
$D_{e \min}$	410 mm	Minimum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius
E	409,9 mm	Raceway diameter outer ring

Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
s	5 mm	Axial displacement
d_1	359 mm	Maximum rib diameter inner ring
$D_1 \min$	398 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia