


SL185008-A-C4

Cylindrical roller bearing

Cylindrical roller bearing SL1850...-A, full complement roller set, two-row, semi-locating bearing, 1 rib on outer ring, 3 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	68 mm	Outside diameter
B	38 mm	Width
C _r	100.000 N	Basic dynamic load rating, radial
C _{0r}	133.000 N	Basic static load rating, radial
C _{ur}	18.400 N	Fatigue load limit, radial
n _G	6.300 1/min	Limiting speed
n _{gr}	4.200 1/min	Reference speed
≈m	0,535 kg	Masa



Mounting dimensions

d _{c min}	50,5 mm	Minimum shaft shoulder
d _{a min}	50,5 mm	Minimum diameter shaft shoulder
D _{a max}	57,1 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum recess radius
r _{a1 max}	1,5 mm	Maximum recess radius
D _{e min}	57,1 mm	Minimum diameter of housing shoulder

Dimensions

r _{min}	1 mm	Minimum chamfer dimension
r _{1 min}	1,5 mm	Minimum chamfer dimension
s	1,5 mm	Axial displacement
C	19 mm	Distance to lubrication hole
d ₁	50,5 mm	Maximum rib diameter inner ring
D _{1 min}	57,1 mm	Minimum rib diameter outer ring
E	61,74 mm	Raceway diameter outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia