




SL192316-C3

Cylindrical roller bearing

Informacje techniczne



Twoja aktualna wersja produktu

Number of rows	1	Single-row design
----------------	---	-------------------

Main Dimensions & Performance Data

d	80 mm	Bore diameter
D	170 mm	Outside diameter
B	58 mm	Width
C _r	475.000 N	Basic dynamic load rating, radial
C _{0r}	560.000 N	Basic static load rating, radial
C _{ur}	82.000 N	Fatigue load limit, radial
n _G	2.600 1/min	Limiting speed
n _{gr}	1.820 1/min	Reference speed
m	6,179 kg	Masa



Dimensions

D ₁	142,1 mm	Shoulder diameter outer ring
D _{a max}	142 mm	Maximum diameter of housing shoulder
d ₁	109,5 mm	Shoulder diameter inner ring
d _{a min}	98 mm	Minimum diameter shaft shoulder
d _{c min}	109,5 mm	Minimum shaft shoulder
F	98,2 mm	Raceway diameter inner ring
r _{a max}	2,1 mm	Maximum fillet radius
r _{min}	2,1 mm	Minimum chamfer dimension
s	3,5 mm	Axial displacement

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia