



FAG

UC213-40

Radial insert ball bearing

Radial insert ball bearings UC, spherical outer ring, location by grub screws, RSR seals on both sides

Informacje techniczne



Main Dimensions & Performance Data

d	63,5 mm	Bore diameter
d	63,5 mm	Bore diameter, inch
D _{SP}	120 mm	Outside diameter
B	65,1 mm	Width
C _{0r}	40.000 N	Basic static load rating, radial
C _{ur}	2.090 N	Fatigue load limit, radial
C _r	61.000 N	Basic dynamic load rating, radial
≈m	1,79 kg	Masa

Dimensions

C	28 mm	Width, outer ring
C ₂	29,4 mm	Sealing total width
S	25,4 mm	Distance raceway
d ₁	80,85 mm	Rib diameter inner ring
C _a	8,2 mm	Distance to lubrication hole
A	12 mm	Distance thread

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Calculation factors

f ₀	14,4	Calculation factor
----------------	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna