


FAG

UCF204

Flanged housing unit

Flanged housing unit UCF

Informacje techniczne



Twoja aktualna wersja produktu

|          |    |                |
|----------|----|----------------|
| Material | GG | Grey cast iron |
|----------|----|----------------|

Main Dimensions & Performance Data

|                 |          |                                   |
|-----------------|----------|-----------------------------------|
| d               | 20 mm    | Bore diameter                     |
| L               | 86 mm    | Flange width                      |
| U               | 33,3 mm  | Total height unit                 |
| C <sub>r</sub>  | 13.600 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 6.600 N  | Basic static load rating, radial  |
| C <sub>ur</sub> | 345 N    | Fatigue load limit, radial        |
| ≈m              | 0,596 kg | Masa                              |

Mounting dimensions

|                |       |                          |
|----------------|-------|--------------------------|
| J              | 64 mm | Distance fixing bore     |
| N              | 12 mm | Fixing bore              |
| N <sub>1</sub> | 64 mm | Distance fixing bore     |
| n              | 4     | Number of screwing holes |



Dimensions

|                |         |                                   |
|----------------|---------|-----------------------------------|
| A              | 25,5 mm | Height housing                    |
| A <sub>1</sub> | 12 mm   | Thickness of flange               |
| A <sub>2</sub> | 15 mm   | Distance raceway                  |
| B              | 31 mm   | Width                             |
| Q              | M6      | Connection thread for lubrication |

Additional information

|       |                     |
|-------|---------------------|
| 1     | Number of housings  |
| F204  | Housing             |
| UC204 | Bearing designation |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |