


FAG

UCFA202

Take-up housing unit

Housing units UCFA, cast iron housing, radial insert ball bearing with grub screws in inner ring, RSR seals, for swivel motion

Informacje techniczne



Twoja aktualna wersja produktu

|          |    |                |
|----------|----|----------------|
| Material | GG | Grey cast iron |
|----------|----|----------------|

Main Dimensions & Performance Data

|    |         |                   |
|----|---------|-------------------|
| d  | 15 mm   | Bore diameter     |
| L  | 98 mm   | Length total      |
| U  | 33,3 mm | Total height unit |
| ≈m | 430 g   | Masa              |

Mounting dimensions

|                |       |                      |
|----------------|-------|----------------------|
| N              | 10 mm | Fixing bore          |
| N <sub>1</sub> | 40 mm | Length (slot)        |
| N <sub>2</sub> | 10 mm | Width (slot)         |
| J              | 78 mm | Distance fixing bore |

Dimensions

|                |         |                                   |
|----------------|---------|-----------------------------------|
| A <sub>1</sub> | 12 mm   | Thickness of flange               |
| A <sub>2</sub> | 15 mm   | Distance raceway                  |
| A              | 25,5 mm | Height housing                    |
| V              | 60 mm   | Shoulder diameter housing         |
| W              | 50 mm   | Width housing slot side           |
| Q              | M6      | Connection thread for lubrication |



Additional information

|       |                     |
|-------|---------------------|
| FA204 | Housing             |
| UC202 | Bearing designation |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |