



FAG

UCFL211-32

Flanged housing unit

Flanged housing unit UCFL

Informacje techniczne



Twoja aktualna wersja produktu

|          |    |                |
|----------|----|----------------|
| Material | GG | Grey cast iron |
|----------|----|----------------|

Main Dimensions & Performance Data

|                 |          |                                   |
|-----------------|----------|-----------------------------------|
| d               | 50,8 mm  | Bore diameter                     |
| L               | 130 mm   | Flange width                      |
| H               | 224 mm   | Height flange                     |
| U               | 58,4 mm  | Total height unit                 |
| C <sub>r</sub>  | 46.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 29.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 1.520 N  | Fatigue load limit, radial        |
| ≈m              | 3,02 kg  | Masa                              |

Mounting dimensions

|   |        |                          |
|---|--------|--------------------------|
| J | 184 mm | Distance fixing bore     |
| N | 19 mm  | Fixing bore              |
| n | 2      | Number of screwing holes |



### Dimensions

|                |         |                                   |
|----------------|---------|-----------------------------------|
| A              | 43 mm   | Height housing                    |
| A <sub>1</sub> | 20 mm   | Thickness of flange               |
| A <sub>2</sub> | 25 mm   | Distance raceway                  |
| B              | 55,6 mm | Width                             |
| Q              | M6      | Connection thread for lubrication |

### Additional information

|          |                     |
|----------|---------------------|
| 1        | Number of housings  |
| FL211    | Housing             |
| UC211-32 | Bearing designation |

### Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |