



FAG

UCT217

Take-up housing unit

Housing units UCT, cast iron housing, radial insert ball bearing with grub screws in inner ring, RSR seals, for linear motion

Informacje techniczne



Twoja aktualna wersja produktu

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	85 mm	Bore diameter
H	198 mm	Height
L	260 mm	Length total
C _{0r}	64.000 N	Basic static load rating, radial
C _{ur}	3.050 N	Fatigue load limit, radial
C _r	88.000 N	Basic dynamic load rating, radial
≈m	10,7 kg	Masa

Mounting dimensions

A ₁	30 mm	Width guidance groove
	0,3 mm	Upper width guidance groove tolerance
	0 mm	Lower width guidance groove tolerance
H ₁	173 mm	Distance guidance grooves
	0 mm	Upper distance guidance groove tolerance
	-0,8 mm	Lower distance guidance groove tolerance
N	48 mm	Fixing bore



Dimensions

L ₁	162 mm	Distance shaft axis
L ₂	29 mm	Length fixed link
L ₃	157 mm	Length guidance groove
A	73 mm	Width housing fixing side
N ₁	38 mm	Width recess
N ₂	73 mm	Height recess
B	85,7 mm	Width inner ring
S ₁	51,6 mm	Distance of raceway to locking collar
T	124 mm	Height housing fixing side
Q	M6	Connection thread for lubrication
A ₂	54 mm	Width housing

Additional information

T217	Housing
UC217	Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.