




ZKLFA0850-2RS

Axial angular contact ball bearing

Angular contact ball bearing units
ZKLFA...2RS, double direction, for screw
mounting, lip seals on both sides, with
flattened flange

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2RS	Contact lip seal on both sides
---------	-----	--------------------------------

Main Dimensions & Performance Data

d	8 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,005 mm	Bore diameter lower tolerance
D	32 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,01 mm	Outside diameter lower tolerance
B	20 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C _a	12.500 N	Basic dynamic load rating, axial
C _{0a}	16.300 N	Basic static load rating, axial
C _{ua}	740 N	Fatigue load limit, axial
n _G Grease	12.100 1/min	Limiting speed for grease lubrication
n _g	5.100 1/min	Thermally permissible speed
≈m	0,131 kg	Masa



14.09.2026, 20:02:21 UTC

SCHAEFFLER



Dimensions

Temperature range

Additional information

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne