


**ZKLN3072-2Z-XL**

Axial angular contact ball bearing

Axial angular contact ball bearings
ZKLN...-2Z, double direction, gap seals on
both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2Z	Minimal gap seal on both sides
Tolerance class	Standard	

Main Dimensions & Performance Data

d	30 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,005 mm	Bore diameter lower tolerance
D	72 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,01 mm	Outside diameter lower tolerance
B	38 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C _a	65.000 N	Basic dynamic load rating, axial
C _{0a}	108.000 N	Basic static load rating, axial
C _{ua}	6.500 N	Fatigue load limit, axial
n _G Grease	5.600 1/min	Limiting speed for grease lubrication
n _g	4.000 1/min	Thermally safe operating speed
M _R	0,4 Nm	Bearing frictional torque
≈m	0,736 kg	Masa



Mounting dimensions

D _a max	64 mm	Maximum diameter of housing
d _a min	47 mm	Minimum diameter shaft

Dimensions

d ₁	51 mm	Rib diameter inner ring
r _{min}	0,3 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension
α	60 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

c _{aL}	950 N/μm	Rigidity axial
c _{kL}	400 Nm/mrad	Tilting rigidity
M _m	1,91 kg*cm2	Mass moment of inertia
	2,5 μm	Axial runout
	ZMA30/52	Recommended INA precision locknut for radial locking
	AM30	Recommended INA precision locknut for axial locking
M _A	65 Nm	Tightening torque for the recommended INA precision locknut
	19.509 N	Required locknut force axial



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne