




ZKLN3572-2Z-XL

Axial angular contact ball bearing

Axial angular contact ball bearings
ZKLN...2Z, double direction, gap seals on both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2Z	Minimal gap seal on both sides
Tolerance class	Standard	

Main Dimensions & Performance Data

d	35 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,005 mm	Bore diameter lower tolerance
D	72 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,01 mm	Outside diameter lower tolerance
B	34 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C _a	45.000 N	Basic dynamic load rating, axial
C _{0a}	89.000 N	Basic static load rating, axial
C _{ua}	5.400 N	Fatigue load limit, axial
n _G Grease	5.800 1/min	Limiting speed for grease lubrication
n _g	3.800 1/min	Thermally safe operating speed
M _R	0,3 Nm	Bearing frictional torque
≈m	0,648 kg	Masa



Mounting dimensions

D a max	62 mm	Maximum diameter of housing
---------	-------	-----------------------------

d a min	45 mm	Minimum diameter shaft
---------	-------	------------------------

Dimensions

d 1	52 mm	Rib diameter inner ring
-----	-------	-------------------------

r min	0,3 mm	Minimum chamfer dimension
-------	--------	---------------------------

r 1 min	0,6 mm	Minimum chamfer dimension
---------	--------	---------------------------

α	60 °	Contact angle
---	------	---------------

Temperature range

T min	-30 °C	Operating temperature min.
-------	--------	----------------------------

T max	120 °C	Operating temperature max.
-------	--------	----------------------------

Additional information

c aL	900 N/μm	Rigidity axial
------	----------	----------------

c kL	400 Nm/mrad	Tilting rigidity
------	-------------	------------------

M m	1,51 kg*cm2	Mass moment of inertia
-----	-------------	------------------------

	2,5 μm	Axial runout
--	--------	--------------

	ZM35	Recommended INA precision locknut for radial locking
--	------	--

	AM35/58	Recommended INA precision locknut for axial locking
--	---------	---

M A	40 Nm	Tightening torque for the recommended INA precision locknut
-----	-------	---

	10.770 N	Required locknut force axial
--	----------	------------------------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne